

speco technologies™

LCD Monitor with Wireless 4 Channel CCTV Receiver



VMW-2.5LCD

Features

- 2.4Ghz mobile wireless monitor • Runs on batteries or included power supply
- 2.5" LCD screen - 480 x 234 • 4 channels for multiple camera use • Handles video and audio
- Video output connector allows for connection to a monitor, VCR or DVR • Fits in the palm of your hand
- Works with cameras connected to our WT-2500

Specifications

Type	TFT
Size	2.5"
Resolution	480 x 234
Active Area	1.94" x 1.5"
Dot Pitch	0.1025mm x 0.163mm
View Angle (U/D/L/R)	10°/30°/45°/45° (Min.)
Brightness	250 cd/m2
Contrast Ratio	150:1
Interface	Alternated video signal
Light Source	CCFL*
RF Modulation/Demodulation	FM
Input VSWR	2:1
Receiving Frequency	2,400MHz~2,483MHz - 4 selectable channels
Intermediate Frequency	480MHz
Frequency Stabilization	±100kHz
Local Leakage at Input Terminal	≤-55dbm
Receiving Sensitivity	≤-80dbm
Power Supply	5 Volts DC power supply included
Power Consumption Current	700mA
Operating Temperature	0°C~50°C / 32°F~122°F
Storage Temperature	-20°C~80°C / -4°F~176°F
Operating Humidity	85%RH
Dimensions (W)x (L)x (H)	5.12" x 3.15" X 1.5"
Weight	8.19 oz

* CCFL-Cold-Cathode Fluorescent Lamps

* Channel Frequency--CH1=2,414MHz; CH2=2,432MHz; CH3=2,450MHz; CH4=2,468MHz

Package Includes:

VWM-2.5LCD	Power Supply	Instructions
Warranty card	Battery	Carry Pouch
Ear Plug		

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880